

# GROUND WATER SURVEY CONSULTANCY

GEOLOGISTS, GEOPHYSICISTS & TUBEWELL ENGINEERS

## GEO-PHYSICAL WELL ELECTROLOGGING REPORT

Ref No:- 553

Date:- 23-07-2022

### NAME OF SITE

GRAM PANCHAYAT- Karimpur Mubarak      BLOCK- Nahtaur      DISTT- Bijnor

### NAME OF AGENCY

LC Infra Projects Pvt. Ltd.- TCEL(JV)  
Bijnour



## GROUND WATER SURVEY CONSULTANCY

Electric Well Logging, Geophysical Resistivity Survey, Ground Water Investigations.

112 A-Shree Nagar Colony, Firozabad Road, Agra- 282006

(M) : 9412260823, 9794625420, 9761163000, Email : gwsc\_agra@yahoo.com

**ISO ; 9001 : 2015**

Ground Water Survey Consultancy



# REPORT ON GEOPHYSICAL WELL LOGGING AT

GRAM PANCHAYAT- KARIMPUR MUBARAK, BLOCK- NEHTAUR, DISTT- BIJNOR  
UNDER  
JAL JIVAN MISSION

## Introduction :

A Deep bore hole was drilled 160 mtrs. depth. and Logged depth 155 mtrs. at above site. Was drilled by M/s LC Infra Projects Pvt. Ltd.- TCEL(JV), Bijnour.

On the request of M/s LC Infra Projects Pvt. Ltd.- TCEL(JV), Bijnour. a Geophysical well Logging in the above bore hole using IGIS Well Logger on 23.July.2022.

Logging Para meters - Self potential, short normal (N-16), Long Normal (N-64), Lateral. Details of major aquifer formations explored from logging of bore hole combined with the study of Strata Chart prepared from drill cuttings are given in the following table:-

S.No.	Depth range(m)	Thickness(m)	Lithology	Expected Water Quality
1.	0 - 5	5	Surface soil	
2.	5 - 11	6	Dry sand	
3.	11 - 30	19	Sandy Clay	
4.	30 - 36	6	Clay kankar	
5.	36 - 40	4	Fine sand	Good
6.	40 - 62	22	Sandy Clay	
7.	62 - 114*	52	Medium sand	Good
8.	114 - 120	6	Clay kankar	
9.	120 - 130*	10	Medium sand	Good
10.	130 - 135	5	Clay kankar	
11.	135 - 145*	10	Medium sand	Good
12.	145 - 155	10	Clay kankar	



**Conclusions and Recommendations :-**

1. The Lithology broadly tallies with that of drill cutting strata chart.
2. The zones marked with asterisk (\*) appear to be aquifer zones for possible development of tubewell.
3. The Quality of water is expected Good.
4. Expected discharge is 900 to 1000 L.P.M.
5. It is recommended to have a chemical and bacteriological analysis of the water sample before using it for human consumption or for any other use.
6. All projections and recommendations are subject to the inherent limitations of the technique employed and there could be variations as the underground conditions are not always amenable to physical interpretations.

**Geophysicist**



**Ground Water Survey Consultancy**