GROUND WATER SURVEY CONSULTANCY

GEOLOGISTS, GEOPHYSICISTS & TUBEWELL ENGINEERS

GEO-PHYSICAL WELL ELECTOLOGGING REPORT

Ref No:- 601

Date:- 09-03-2022

NAME OF SITE

GRAM PANCHAYAT- Dolapur

BLOCK- Jalalabad

DISTT- Shahjanhapur

NAME OF AGENCY

M/s NCC Ltd. Shahjanhapur



GROUND WATER SURVEY CONSULTANCY

Electric Well Logging, Geophysical Resistivity Survey, Ground Water Investigations.
112 A-Shree Nagar Colony, Firozabad Road, Agra- 282006
(M): 9412260823, 9794625420, 9761163000, Email: gwsc_agra@yahoo.com

ISO; 9001: 2015

Ground Water Survey Compultancy

REPORT ON GEOPHYSICAL WELL LOGGING

GRAM PANCHAYAT- DOLAPUR, BLOCK- JALALABAD DISTT- SHAHJANHAPUR UNDER JAL JIVAN MISSION

Introduction:

A Deep bore hole was drilled 122 mtrs. depth. and Logged depth 120 mtrs. at above site. Was drilled by M/S NCC Ltd., Shahajanhapur.

On the request of M/S NCC Ltd., Shahajanhapur. a Geophysical well Logging in the above bore hole using IGIS Well Logger on 09.Mar.2022.

Logging Para meters - Self potential, short normal (N-16), Long Normal (N-64), Lateral. Details of major equifer formations explored from logging of bore hole combined with the study of Strata Chart prepared from drill cuttings are given in the following table:-

0 - 5 5 - 10	Thickness(m) 5	Lithology Surface soil	Expected Water Quality
5 - 10	5		Water Quality
5 - 10	5		
	5 5		
10 20		Dry sand	
	20	Sandy clay	
	8		
	4	Fine to Medium sand	Med. to Good
	8		Wied. to Good
	35		Mad to Cont
	15		Med. to Good
100 - 120*	20		Med, to Good
	10 - 30 30 - 38 38 - 42 42 - 50 50 - 85* 85 - 100 100 - 120*	30 - 38 8 38 - 42 4 42 - 50 8 50 - 85* 35 85 - 100 15	10 - 30 20 Sandy clay 30 - 38 8 Clay kankar 38 - 42 4 Fine to Medium sand 42 - 50 8 Clay kankar 50 - 85* 35 Medium sand 85 - 100 15 Clay kankar

Ground Water Survey Consultancy

Conclusions and Recommendations :-

- 1. The Lithology broadly tallies with that of drill cutting starta chart.
- The zones marked with asterisk (*) appear to be aquifer zones for possible development of tubewell.
- The Quality of water is expected Medium to Good.
- 4. Expected discharge is 900 to 1000 L.P.M.
- It is recommended to have a chemical and bacteriological analysis of the water sample before using it for human consumption or for any other use.
- 6. All projections and recommendations are subject to the inherent limitations of the technique employed and there could be variations as the underground conditions are not always amenable to physical interpretations.

Geophysicist

Ground Water Survey Consultancy

And the state of t Pics N 1988/ N 1988/ S S -011 8 9 8 g -05 B ş ö 20ä 5 3 5-ㅈ-2 않-8-35-8 8-5-2 **5**-뜽-60 65 Depth(m) 5 강-8-23-8-8-8-**5**-; ᇙ-중-ᅜᆜᅩ

