GROUND WATER SURVEY CONSULTANCY GEOLOGISTS, GEOPHYSICISTS & TUBEWELL ENGINEERS

.oLodis13, GLoi 11131Cis15 & 1622 W 222 21 1611 =

GEO-PHYSICAL WELL ELECTOLOGGING REPORT

Ref No:- 509

Date: - 25-02-2022

NAME OF SITE

GRAM PANCHAYAT- Bhatiura Buzurg BLOCK- Powayan DISTT- Shahjanhapur

NAME OF AGENCY

M/s NCC Ltd. Shahjanhapur



GROUND WATER SURVEY CONSULTANCY

Electric Well Logging, Geophysical Resistivity Survey, Ground Water Investigations.
112 A-Shree Nagar Colony, Firozabad Road, Agra- 282006
(M): 9412260823, 9794625420, 9761163000, Email: gwsc agra@yahoo.com

ISO; 9001: 2015

Ground Water Shirt Consultancy
Agra

REPORT ON GEOPHYSICAL WELL LOGGING

GRAM PANCHAYAT- BHATIURA BUZURG, BLOCK- POWAYAN DISTT- SHAHJANHAPUR UNDER JAL JIVAN MISSION

Introduction:

A Deep bore hole was drilled 120 mtrs. depth. and Logged depth 120 mtrs. at above site. Was drilled by M/S NCC Ltd., Shahajanhapur.

On the request of M/S NCC Ltd., Shahajanhapur. a Geophysical well Logging in the above bore hole using IGIS Well Logger on 25.Feb.2022.

Logging Para meters - Self potential, short normal (N-16), Long Normal (N-64), Lateral. Details of major equifer formations explored from logging of bore hole combined with the study of Strata Chart prepared from drill cuttings are given in the following table:-

S.No.	Defth range(m)	Thickness(m)	Lithology	Expected Water Quality
1	0 - 5	5	Surface soil	
2.	5 - 20	15	Fine to Medium sand	
3.	20 - 25	5	Clay kankar	
4.	25 - 35	10	Medium sand	Good
5.	35 - 40	5	Clay kankar	
6.	40 - 49*	9	Medium sand	Good
7.	49 - 55	6	Clay kankar	
8.	55 - 65*	10	Medium sand	Good
9.	65 - 70	5	Clay kankar	
10.	70 - 76*	6	Fine to Medium sand	Good
	76 - 85	9	Clay kankar	
11.	85 - 114*	29	Medium sand & Kankar	Good
12.	114 - 120	6	Clay kankar	



Conclusions and Recommendations:

- 1. The Lithology broadly tallies with that of drill cutting starta chart.
- 2. The zones marked with asterisk (*) appear to be aquifer zones for possible development of tubewell.
- 3. The Quality of water is expected Good.
- 4. Expected discharge is 900 to 1000 L.P.M.
- 5. It is recommended to have a chemical and bacteriological analysis of the water sample before using it for human consumption or for any other use.
- 6. All projections and recommendations are subject to the inherent limitations of the technique employed and there could be variations as the underground conditions are not always amenable to physical interpretations.

Ground Water Survey Consultancy

Agency Manual
Langling Samuel
Langling Samuel Per Herson 8 Ohm m 9 ş -08 70-8 5 26 20-20-÷ ö ĕ 0-5-5 8-K-8 **#**-6-5-8-:5-Depth(m) 8-7 강. 8-8-8-Vieland 9-ਡ-호-; ₹-8-1

