

Lowering of T.W. Assembly at Sikra Bargah T.W. Bore

Drilling/Lowering - 132/20

T.W. Assembly Size - 200X150mm

Bore Size - 550X500mm

Recommended Discharge - 450 L.P.M

S.W.L. - 5 feet

D.O.L. - 24/10/20

Logging Report.

1. 12-28 - 16m	6.12	0.50m	
2. 54-67 - 13m	6.00		
3. 72-86 - 14m	6.13		
4. 90-97 - 7m	6.13		
5. 104-114 - 10m	6.12		
6. 117-130 - 13m	6.12		
	6.12		
	6.12		
	6.12		
	6.10		
<u>Strata as Per Actual</u>			
0 - 10m clay			
10 - 30m M.Sand		0.15m	60-58m
30 - 55m clay	6.01		60-73m
55 - 64m M.Sand	6.01	18.04m	
64 - 70m clay	6.02		
70 - 85m F.to M.Sand			78-77m
85 - 89m clay		6.02m	84-79m
89 - 93m F.to M.Sand	5.70	5.70m	90-49m
99 - 103m clay		6.01m	96-50m
103 - 131m F.to M.Sand	6.01		
131 - 135m clay	5.00	11.01m	107-51m
		6.00m	
			113-51m
	6.01	6.01m	
			119.52m
			AGL (+) 0.50m
			<u>total 120.02m</u>

OCTOBER

M	5	12	19	26
T	6	13	20	27
W	7	14	21	28
T	8	15	22	29
F	9	16	23	30
S	10	17	24	31
S	4	11	18	25

(M/S Jai Prakash Chaudhary) (Sampuranand) (Babban Yadav) (Adarsh Verma)  
 Contractor J.E. A.E. E.E.